

TESCORP TES-LUBE LUBRICATION SYSTEM

Safe, Dependable, Protects Compressors, Reduces Man-hours

Now you can protect your compressors from burn-out or failure due to loss of lubrication.

15- or 30-Gallon Storage Tanks:

- » Allow up to one month of continuous operation between refills, reducing man-hours and risks of water contamination.

Direct-driven Pumping Unit:

- » Enclosed motor eliminates risk of system failure due to belt breakage

25 Micron Filter:

- » Removes entrained impurities in the lubricant

Digital No-flow Timer (DNFT):

- » Monitors movement of divider piston for dependable "timed" shutdown protection. Not affected by temperature or oil viscosity. Requires no external power.

Liquid Crystal Display:

- » Incorporates a liquid crystal display that accurately indicates lube-cycle time

Protects your valuable compressors against lube failure:

- » Safe and dependable compressor lubrication
- » Helps protect compressors against lube failure
- » Virtually eliminates major causes of water contamination
- » Reduces man-hours

Tes-Lube System:

- » Is designed to keep your workhorse machinery safely and precisely lubricated for as long as 30 days without refilling, eliminating major causes of water contamination

Tes-Lube's Distribution Block:

- » Smoothly and continuously disburses lubricants to critical parts, safely powered by an enclosed direct-drive pump

Tes-Lube Duplex:

- » One common storage tank serves two compressors. Lube flow can be isolated to each compressor

